

AVANI – SOFT

GRAPHIC SOFTWARE

General

Avani Graphic software is the best solution avaliable for the representation of the location for the Avani Fire Alarm system in graphical form. The graphical representation enables the user to monitor the real time fire, navigate the location of the fire and control the Fire alarm System remotely.



Features

- User friendly with windows based software.
- Three Level Multi User Access.
- Multi Mode (Ethernet / USB)Communication Facility.
- Facility to monitor and Control the fire alarm control panels from a single window.
- Unambiguous Visual & Audible alerts for fire and fault conditions.

- Pop up for any events like fire, fault, power fault, etc.
- Event Fetch from fire alarm control panel facility.
- Single / Multi Mode Floor Configuration facility.
- Floor Configuration using DWG / DXF Files.
- Maximum of 32 AVANI addressable fire alarm control panels shall be monitored and controlled through the software.

Screenshot

Site Details



FACP Control Panel



Speech Configuration



Event Log



PC Specification

Windows 8.1 (with update 2919355) & above ('Home' package variants can be used if network connectivity is not required) Monitor (minimum 17" and support a screen resolution 1024 X 768) Required Required for software installation (Optional)
Monitor (minimum 17" and support a screen resolution 1024 X 768) Required Required for software installation (Optional)
Required for software installation (Optional)
Required for software installation (Optional)
40Gb Hard Drive (Minimum Recommended)
Backup device recommended (e.g. CDR, USB, ZIP disk)
USB Port for communications with Graphics Interface. (Additional serial
ports may be necessary if connectivity to other services are required)
Windows compatible soundcard & speakers / On-board sounder
required for event notification
4 GB RAM (Minimum Recommended)
Intel Pentium 4 Processor, 1.8 Ghz or higher
Dedicated to Fire Alarm Systems
 Any resolution above above 1024 X 768 can be supported however, Graphical bitmaps must be created in the appropriate format for the resolution selected.
 If monitors are to be used in Portrait manner a horizontal screen resolution of at least 950 pixels must be available.
Optical Mouse Required
XGA Graphics Accelerator supporting a minimum 1024 X 768 resolution

Compatible Devices

Model	Description
AVANI	Analogue Addressable Fire alarm Control Panel expandable upto 4 loop

Ordering Information

Model	Description
AVANI – SOFT	Graphic Software