

# RE-125 / RE-250 PA Amplifier

## Features

- Better Sound quality.
- 19", 2U rack mountable.
- Low power consumption.
- System on Indication.
- Volume Control facility.
- Class D Amplifier.
- Low Heat dissipation.
- Compact size.



## Specification

| Electrical Specification     |   |
|------------------------------|---|
| <i>Primary Power</i>         | 220VAC ± 10%, 50 Hz.                                |
| <i>Standby Voltage</i>       | 24 VDC  |
| <i>Maximum DC Current</i>    | 10 Amps   |
| <i>Audio output</i>          | 100 V   |
| <i>Maximum Watts</i>         | 125 / 250 Watt                                      |
| <i>Audio Input</i>           | From main console                                   |
| <i>Dimensions(2U)</i>        | (484 W X 88 H X 325D)mm                             |
| <i>Operating Temperature</i> | 0 - 49° C / 32-120° F.                              |
| <i>Relative Humidity</i>     | 93 ± 2% RH (non-condensing) at 32 ±2° C / 90 ±3° F. |

## Compatible Panel

| Model    | Description                        |
|----------|------------------------------------|
| Revac nx | Conventional Public Address System |
| e'Scape  | Addressable Public Address System  |

## Ordering Information

| Model  | Description     |
|--------|-----------------|
| RE-125 | 125 W Amplifier |
| RE-250 | 250 W Amplifier |

### India

RAVEL ELECTRONICS PVT LTD.,  
150A, Electronics Industrial Estate,  
Perungudi, Chennai – 96, India.  
E-mail: [marketing@ravelfire.com](mailto:marketing@ravelfire.com); Web: [www.ravelfire.com](http://www.ravelfire.com)

### UAE

RAVEL DMCC,  
Unit No: G30, DMCC Business Center,  
Level No 13, AG Tower, Dubai, UAE.  
E-mail: [sales@raveldmcc.com](mailto:sales@raveldmcc.com)

### USA

RAVEL AMERICAS INC.,  
2855 NW 112<sup>th</sup> Ave ST#2 Miami,  
Doral, Florida 33172, USA.