

RE-316S-2L

CONVENTIONAL PHOTOELECTRIC SMOKE DETECTOR

General

The conventional smoke detectors are designed to work with all conventional Panels. These detectors are low profile and have dual LED's for 360° visual indication. The blinking LED's indicate normal operating conditions whereas the steady state to indicate fire status. It has an unique protocol chamber designed to sense smoke produced by wide range of sources of combustion. It has a unique drift compensation feature wherein the detector adjusts its normal reference based on environment conditions.

Features

- UL listed.
- Dual LED's for 360° visibility.
- Advanced detection technique.
- Polarity free wiring
- Easy to install.
- Sleek low-profile housing design.
- Regular 100mm base.






Specification

1

	Electrical Specification	
Operating Voltage	9 ~ 33V DC.	
Reset Voltage	Less than 1V.	
Standby Current	50 μΑ.	
Start up Time	60 Sec.	
Start up Current	170 μΑ.	
Alarm Current	90 mA (max).	
Remote Output	15mA maximum open collector.	
Smoke Sensitivity	(1.96 ± 0.76) % / ft obscuration	
Air Velocity	0 - 4000 fpm.	
Operating Temperature	-10° C to 37.8° C	
Storage Temperature	$-10\degree$ C to $60\degree$ C.	
Humidity	0 - 95% RH, non-condensing.	
Installation Space	5 meters.	
Mechanical Specification		
Dimension	46 H x 100 D (mm)	
Weight	130 g with base	
IP Rating	IP42	

RE-316S-2L / DS / Rev 03 / 2023-24

Wiring Diagram



Note:

RI-Response Indicator

Compatible Device

Model	Description
RE-314B	Normal Base
RE-717MZ	Addressable Zone Interface Module

Compatible Panel

Model	Description
RE-102	Conventional 2 IDC Fire Alarm Control Panel
RE-104	Conventional 4 IDC Fire Alarm Control Panel
RE-102R	Plastic Conventional 2 IDC Fire Alarm Control Panel
RE-104R	Plastic Conventional 4 IDC Fire Alarm Control Panel
RE-2554	Conventional 4 IDC Fire Alarm Control Panel
RE-2558	Conventional 8 IDC Fire Alarm Control Panel
RE-900 Series	Conventional Fire Alarm Control Panel
RE-25AR	Conventional Agent Release Control Panel
RE-120GR	Conventional Gas Release Control Panel

Ordering Information

Model	Description
RE-316S-2L	Conventional Photoelectric Smoke Detector with Base

E-mail: sales@ravelfire.com; Web: www.ravelfire.com

UAE

USA