

# RE-LU100XT

## P.A HORN SPEAKER

### Specification

Electrical Specification	
<i>Input Power</i>	15W (RMS) 24W (max)
<i>Tapping</i>	COM, 3.75W, 7.5W, 15W
<i>Impedance</i>	100V Line
<i>Frequency Response</i>	275 – 7000 Hz
<i>Type</i>	ABS plastic
<i>Size</i>	205 Diax 271 L
<i>SPL (@1KHz)</i>	106dB
<i>Weight (Approx.)</i>	1.7Kg



RE-LU100XT have been provided with 100V line Matching Transformer with multiple taps easily selectable by changing the rotary switch at the rear of the sealed assembly.

HORN FLARE	: ABS RESIN, OPAL WHITE
REFLECTOR HORN	: ABS RESIN, DARK GRAY
REAR COVER	: ABS RESIN, DARK GRAY
'U' BRACKET	: C.R.C., DARK GRAY, POWDER COATING
SCREWS AND BOLTS	: M.S.
SPEAKER CABLE	: P.V.C. CABLE

### Ordering Information

Model	Description
RE-LU100XT	P.A Horn Speaker

#### India

RAVEL ELECTRONICS PVT LTD.,  
150A, Electronics Industrial Estate,  
Perungudi, Chennai – 96, India.  
E-mail: [sales@ravelfire.com](mailto:sales@ravelfire.com); Web: [www.ravelfire.com](http://www.ravelfire.com)

#### UAE

RAVEL DMCC,  
Unit No: G30, DMCC Business Center,  
Level No-13, AG Tower, Dubai -UAE  
E-mail: [sales@raveldmcc.com](mailto:sales@raveldmcc.com)

#### USA

RAVEL AMERICAS INC.,  
2855 NW 112<sup>th</sup> Ave ST#2 Miami,  
Doral, Florida 33172, USA.  
E-mail: [sales.us@ravelfire.com](mailto:sales.us@ravelfire.com)