

RE-717PT

Printer Interface Module



Product Overview

RE-717PT is a printer with Interface module connects the serial printer with a compatible Fire Alarm Control Panel (FACP) to print real-time logs of system events, detector status reports, and event histories. RE-717PT printer has a serial interface.

Features

- Ultra small size printer.
- Very silent printing thru direct thermal printing method.
- High speed(50mm/sec, MAX)
- High resolution(203dpi : 8dots/mm).
- Serial Interface Printer.
- Support text and graphic printing.
- Easier paper loading by CLAMSHELL design.
- Easier maintenance with self-diagnostics.
- Flow control : Software (XON/XOFF)
- Hardware flow control not supported in printer.



Specifications

Input Power	:	24VDC
Operating Temperature	:	-10°C to 50°C
Storage Temperature	:	-10°C to 70°C
Operating Humidity	:	30 - 80%
Storage Humidity	:	10 - 90%
Weight Including roll paper	:	153 g
Interface	:	Serial Interface
Printing method	:	Digital Thermal Line Printing
Printing speed	:	50mm/sec (max)
Resolution	:	203dpi, 8 dots/mm
Characters per Line	:	42 CPL

Note

External Power Supply required.

Compatibility:

Model	Description
Avani	Addressable FACP

Ordering Information:

Model	Description
RE-717PT	Printer Interface Module

India:

RAVEL ELECTRONICS PVT LTD.,

(An ISO 9001 Company)

150A, Electronics Industrial Estate, Perungudi, Chennai - 96 .India.
E-Mail: marketing@ravelfire.com; Web : www.ravelfire.com

United Kingdom:

RAVEL ELECTRONICS LTD.,

Unit 11, Chancel Industrial Estate, Newhall street,
Willenhall WV13 1NX, West Midlands, United Kingdom.
E-mail: info@ravelfire.co.uk ;Web: www.ravelfire.co.uk